

# DT-X93Hx2

## Dual 9" Full HD Broadcast Rack LCD Monitor

# ProHD



### ■ Features

- ◆ 9" IPS LCD×2, 1920×1200, H/V 170° viewing angle
- ◆ 19" 4U Rack mount with ±30° rotatable
- ◆ 2K/3G/HD/SD-SDI, HDMI, CVBS monitoring
- ◆ 2-ch SDI/HDMI/Analog audio meters with alert
- ◆ Peaking focus assist, Zebra stripes
- ◆ H/V delay, Freeze Frame, AFD, Timecode
- ◆ False color, R/G/B/Mono, 100% internal colorbar
- ◆ Image Flip and Rotate
- ◆ TSL 3.1/4.0 UMD
- ◆ Front TALLY light and GPI control
- ◆ USB firmware upgrade

### ■ Package includes



4-pin XLR power adaptor

### ■ Specification

LCD Performance		
Size	9 inches	
Display area	191.5×119.7 mm	
Resolution	1920×1200	
Color	8 bit	
Aspect ratio	16:9 / 4:3	
Brightness	450 cd/m <sup>2</sup>	
Contrast	1000:1	
Viewing Angle	H/V:170° /170°	
Input/output		
Input Each LCD	BNC×2	2K/3G/HD/SD-SDI input×2
	BNC×1	CVBS input
	HDMI-A×1	HDMI input
	RJ45×1	UMD, GPI input
	3.5mm×1	analog audio input
Output Each LCD	BNC×2	2K/3G/HD/SD-SDI loop output×2
	BNC×1	CVBS loop output
	HDMI-A×1	HDMI loop output
	3.5mm×1	SDI/HDMI/analog audio output
	Video Format	
SDI	SMPTE-2048-2	2048×1080p (23.98/24/25/29.97/30/50/59.94/60)
		2048×1080i (50/59.94/60)
	SMPTE-425M-A/B	1080p (60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/23.98)
	SMPTE-RP211	1080psf (30/29.97/25/24/23.98)
	SMPTE-296M	720p (60/59.94/50)
SMPTE-125M	480i (59.94)	
ITU-R BT.656	576i (50)	
HDMI	480i/576i/480p/576p	
	1080i (60/59.94/50)	
	720p (60/59.94/50)	
	1080p (60/59.94/50/30/29.97/25/24/23.98)	
1080psf (30/29.97/25/24/23.98)		
CVBS	NTSC/PAL	
General		
Input voltage	DC 6.5V-24V	
Power consumption	36W	
Working temperature	0°C~+40°C	
Working humidity	10%~90%	
Storage temperature	- 15°C~ + 60°C	
Storage humidity	10%~90%	
Dimensions	481×173×96mm, 19" 4RU	
Net weight (main body)	2.8kg	

**JVCKENWOOD Corporation**

Manufactured by: SWIT Electronics Co., Ltd.  
10 Hengtong Road, Nanjing, China P.R.